

Defensive Mechanisms

- Authentication mechanisms
- Host-based mechanisms and procedures
- Network firewalls
- Virtual private networks (VPNs)
- Encryption

SE 4C03 Winter 2002

09. Defense Mechanisms

Instructor: W. M. Farmer

Revised: 22 March 2002

1

3

Defensive Services

- Authentication (subject, source)
- Access control (network, host, file)
- Data protection (privacy and integrity)
- Monitoring
- Auditing

Host-based Mechanisms and Procedures

3

2

4

User Account Security

- Secure root account
 - Choose a strong password for the root account
 - Change the root password periodically
 - Use different root passwords for different machines
 - Use the root account only for administrative purposes
 - Do not remotely telnet or FTP into a root account
 - Do not su to root during a remote telnet session
- Secure other user accounts
 - Never create a user account without a password
 - Require all users to have strong passwords
- Protect the password file
 - Use shadow passwords

5

File Protection

- Protect the file system
 - Use groups and read, write, and execute permissions
 - Perform regular backups of the file system
- Be careful with SUID and SGID programs
- Encrypt files that need extra protection

6

Access Control of Network Services

- Turn off all unnecessary and dangerous network services (e.g., finger and tftpd)
 - Uninstall the software needed for such a service
 - For a service running under the inetd server, comment out the relevant line in the /etc/inetd.conf file (which maps services to servers)
- Restrict access to network servers using **wrappers**
 - For example, the tcpd server ("TCP Wrapper") which controls access via the hosts.allow and hosts.deny files
- Carefully configure dangerous services such as anonymous FTP and Web services
- Provide Secure Shell (ssh) instead of rlogin, rsh, and rcp

7

Network Firewalls: Definitions

- A **firewall** is a collection of hosts, routers, and other hardware that controls traffic between two parts of a network.
- A **bastion host** is a firewall computer that is heavily protected because it is exposed to attack.
- A **packet filter** is a device that accepts (forwards) or rejects (drops) packets usually on the basis of just the information in the packet's header.
- A **stateful packet filter** is a packet filter that accepts or rejects packets on the basis of what previous packets have been seen as well as on the basis of the information in the packet's header and data.
- A **proxy** is a middleman server that relays client requests and external server replies across a firewall.

8

Benefits and Uses of a Firewall

1. Enables network security to be implemented and administered in highly centralized manner
 - External packet filtering router
2. Can enforce a network security policy
3. Can reduce a network's external exposure to a just small number of hosts
 - Screened gateway
 - External packet filtering router
 - Internal bastion host
4. Can monitor network traffic efficiently
5. Can implement network address translation
6. Can divide an organization's domain into smaller, more manageable units
 - Screened subnet
 - External packet filtering router
 - Perimeter network
 - Internal (choke) filtering router

9

11

Firewall Architectures

- Screening router
 - External packet filtering router
- Dual-homed gateway
 - External bastion host
- Screened gateway
 - External packet filtering router
 - Internal bastion host
- Screened subnet
 - External packet filtering router
 - Perimeter network
 - Internal (choke) filtering router

Packet Filters

1. Activities behind the firewall initiated by insiders
2. Traffic that does not go through the firewall
3. Dangerous code (e.g., a virus) that is legitimately allowed to go through the firewall
 - A packet flowing through a router can be filtered at both the interface where it enters and the interface where it exits
4. New unforeseen threats
 - Packet filters are especially useful for catching source spoofing packets:
 - Packets coming from the outside which have inside source addresses
 - Packets coming into a host which have the loopback address (127.0.0.1) as their source address

10

12

Implementing a Packet Filtering Policy

- Designing a packet filtering policy is not very hard
- Implementing a packet filtering policy with a router can be difficult
 - Configuring packet filters is often akin to assembly language programming
 - The syntax of a filter programming language is often inflexible
 - An implementation involving more than one vendor can be very confusing because different vendors can use different approaches
 - Documentation is often incomplete or incorrect, and the filter devices themselves may not work as documented

13

Packet Filtering Policies

- **The Foundational Packet Filtering Policy:**
 1. No non-TCP packets are allowed through the firewall
 2. TCP connections across the firewall may not be initiated from outside the firewall
 3. No spoofing addresses inside the firewall
- Many packet filtering policies are modifications of the foundational packet filtering policy
- Some services initiated by internal users require packets that violate the Foundational Packet Filtering Policy:
 - UDP-based services
 - ICMP-based services
 - FTP in normal mode
 - X11 clients operating outside the firewall
 - DNS

14

Proxy Servers

- Benefits:
 - Can create virtual UDP and TCP connections and manage them using state information
 - Reduces exposure of internal clients and servers
 - Reduces logins required on firewall hosts
 - Can cache requested information
 - Can translate network addresses
 - Can be transparent to users
- Kinds of proxy servers:
 - Application-level (usually dedicated to a protocol)
 - Circuit-level (usually generic)

15

Steps for Building a Firewall

1. Formulate a network security policy
2. Choose a firewall architecture
3. Configure the firewall hosts (routers and bastion hosts)
 - Pump up hardware, slim down software
 - Plenty of memory, disk space, computing capacity
 - Only software which is absolutely necessary
 - Configure disks with multiple, large partitions
 - No unnecessary user accounts
 - Set up minimal routing tables
 - Turn off ARP
 - No dynamic routing mechanisms
 - Turn off all network services initially
 - Close all packet filters initially

16

Steps for Building a Firewall (cont.)

4. Develop administrative procedures and mechanisms for:
 - Logging
 - File backup
 - Hardware and software upgrading
 - Performance monitoring
 - Intrusion monitoring and response
5. Install the firewall
 - Connect the firewall to the internal and external networks
 - Possibly have a direct connection for emergencies
6. Install network services one at a time
 - Do plenty of testing
 - Use IP addresses instead of domain names